## Flame retardant polycarbonate resin composition and 0 formed articles

2000:457151 CAPLUS

L49 ANSWER 42 OF 139 CAPLUS COPYRIGHT 2001 ACS

```
ACCESSION NUMBER:
                         133:74825
DOCUMENT NUMBER:
                         Nodera, Akio; Kitayama, Masahiro
INVENTOR(S):
                         Idemitsu Petrochemical Co., Ltd., Japan
PATENT ASSIGNEE(S):
                         PCT Int. Appl., 50 pp.
SOURCE:
                         CODEN: PIXXD2
                         Patent
DOCUMENT TYPE:
                         Japanese
LANGUAGE:
FAMILY ACC. NUM. COUNT: 1
PATENT INFORMATION:
                                          APPLICATION NO. DATE
                    KIND DATE
     PATENT NO.
                                          WO 1999-JP7027
                                                            19991215
     WO 2000039217
                            20000706
                     A1
         W: US
         RW: AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL,
             PT, SE
                                                            19981225
                                           JP 1998-368391
                            20000711
                       A2
     JP 2000191897
                      A2
                                           JP 1998-368392
                                                            19981225
                            20000711
     JP 2000191898
                                                            19990818
                                           JP 1999-231118
                            20010227
     JP 2001055500
                      Α2
                                                        A 19981225
A 19981225
                                        JP 1998-368391
PRIORITY APPLN. INFO.:
                                        JP 1998-368392
                                                        A 19990818
                                        JP 1999-231118
     The resin compn. contg. no halogen compds. comprises relative to 100 parts
AB
     of a resin comprising (A) 60-99% of a polycarbonate resin and
     (B) 1-40% of a styrenic resin, 0.1-10 parts of (C) a silicone compd.
     contg. a functional group and 0.02-5% of (D) a fluoroolefin resin. The
     compn. can be used for producing a formed article having satisfactory
     impact resistance and excellent thermal stability while maintaining
     excellent flame retardancy.
     silicone fireproofing agent polycarbonate; polysiloxane
     fireproofing agent polycarbonate blend; impact
     resistant polycarbonate blend
     Polysiloxanes, uses
TΤ
     RL: MOA (Modifier or additive use); USES (Uses)
         (KC 89, fireproofing agents; halogen-free flame retardant
        polycarbonate compns. and formed articles)
     Styrene-butadiene rubber, uses
     RL: MOA (Modifier or additive use); USES (Uses)
         (Me methacrylate-grafted, Metablen C 223; halogen-free flame retardant
        polycarbonate compns. and formed articles)
     Acrylic rubber
 TT
     RL: MOA (Modifier or additive use); USES (Uses)
         (butadiene-Me methacrylate-styrene, graft, Metablen C 223; halogen-free
         flame retardant polycarbonate compns. and formed articles)
      Fireproofing agents
 TT
         (halogen-free flame retardant polycarbonate compns. and
         formed articles)
      Fluoropolymers, uses
      Glass fibers, uses
      RL: MOA (Modifier or additive use); USES (Uses)
         (halogen-free flame retardant polycarbonate compns. and
         formed articles)
      Polycarbonates, properties
      RL: POF (Polymer in formulation); PRP (Properties); USES (Uses)
         (halogen-free flame retardant polycarbonate compns. and
         formed articles)
 IT
      Polymer blends
      RL: PRP (Properties)
          (halogen-free flame retardant polycarbonate compns. and
```